



# V3000 Headrail System Specifications

## Channel

---

- Available in white or anodized
- Aluminum alloy - 1 3/4" wide x 1 1/4" high with .040" minimum wall thickness

## Controls

---

### Cord and Chain System

- Controls are made of acetal plastic which allows for precise control of light using No. 10 nickel-plated steel chain.
- End controls are covered to enclose sprocket
- Traverse cord roller allows extended cord life and ease of operation.
- Gear ratio - Direct Drive Control 1:1

### Wand System

- Equipped with a wand control with a left and right idler end, which holds the tilt rod and covers both ends of the channel
- Controls made of acetal plastic with a reduction gear
- Firmly encircles the tilt rod which provides smooth operation

## Carriers

---

- Molded in acetal plastic with separate straps
- The Syncromatic™ carrier allows for self-alignment and uniform rotation
- Two independent self-lubricating wheels for easy traversing
- Rotation of the vane is controlled by the precision molded rack and pinion gear system
- Replaceable vane clip system (clear plastic) allows for fast and efficient repair without disassembling the headrail

## Rotation

---

### Cord and Chain System

- No. 10 nickel-plated steel chain
- 4 prong tilt rod is made of extruded aluminum
- Tilt rod passes through all the carriers, providing rotation to each vane by means of a precision molded rack and pinion gear system

### Wand System

- Provides 180 degree rotation to each vane simultaneously through a gear system in the control housing, turning the tilt rod

## Stacking

---

- One way draw (left or right) or reverse stack
- Split draw, centre draw
- Blind traverses by means of a synthetic traverse cord or wand control pull

## Spacing

---

- Plastic strap link system
- Normal louver spacing has a minimum overlap of 3/8"
- Clip Link Equalizer provides uniform spacing for 3 1/2" and 2" louvers

## Mounting Hardware

---

- V3000 System has numerous standard clip-on mounting hardware, including ceiling clips, wall or extension brackets

## Size Recommendations

---

- Maximum width 192"
- Maximum drop 120"